

SD-MV-0501 Quick Start Manual

Note


1. Do not fix the device to any surface which is a heat source to avoid over heating
2. Do not cover the surface or ventilation grills of the device to avoid over heating

1. Verify the package contents

Please verify the package contents against the List Below

1. SD-MV-0501 Unit	x1	6. 3-pin Phoenix Connector	X1
2. 24V/1A Power Adapter	x1	7. Download Guide Card	X1
3. Quick Start Manual	x1	8. HDBaseT RX (only with Kit)	X1






2. Set up the SD-MV-0501



- I. Connect the power cable to the unit and power it up
- II. Connect the outputs to the screens via HDMI cable or HDBaseT RX
- III. Connect all the video sources to the inputs of the devices

3. Control SD-MV-0501 via Front Panel



Name	Description
HDMI 1	Press HDMI 1 button to select HDMI 1 as the input source. Long press it for 3 seconds to enter SINGLE mode,  Note, when works on non-SINGLE mode, directly short press input buttons will be invalid.
HDMI 2	Press HDMI 2 button to select HDMI 2 as the input source. Long press it for 3 seconds to enter PIP Multiview mode, 
HDMI 3	Press HDMI 3 button to select HDMI 3 as the input source. Long press it for 3 seconds to enter PBP Multiview mode, 
DP	Press DP button to select DP as the input source. Long press it for 3 seconds to enter 3xWIN mode, 
USB-C	Press USB-C button to select USB-C (video only) as the input Long press it for 3 seconds to enter 4xWIN mode, 
RESO	Press RESO (short for Resolution) button to select different output resolution. The resolution info will be shown on screen. Long press this button for 3 seconds the screen will show up one yellow border on window 1. Continue press this button the border will be shown on window 2 or 3... then press one input button such as HDMI 1, and then HDMI 1 will be displayed on the current selected window.

4. Control SD-MV-0501 via Serial Port

9600 baud rate, 8 data bits, 1 stop bit, no parity. Please refer to SD-MV-0501 User Manual for command lines to control the unit.

This quick start manual provides basic instructions for setting up SEADA SD-MV-0501 seamless switcher with multiview. For additional information about how to use the unit, please refer to the SD-MV-0501 User Manual, which can be downloaded from the SEADA website (<https://seada.co.uk/downloads>).